QMAIL-SMTPD Selctive Relaying
Simplified Receive Process
ENV: $RELAYCLIENT not set !

qmail-smtpd

> *SENDER's E-Mail Address:*
> *abc.def@ghi.xy*
> *SENDER's IP Address:*
> *123.456.789.xyz*
> *RECEIPIENT's E-Mail Address:*
> *no.one@fake.com*

SENDER IP
123.456.789.[xyz]
in my list
?

./control/relayclients

no →

./control/relaydomains

SENDER
DOMAIN NAME
[ghi].xy
in my list
?

yes

yes ←

no

./control/rcpthosts

RECEIPIENT
ADDRESS
[no.one]@fake.com
in my list
?

no → **STOP!**

./control/morercpthosts

yes ←

yes → **STOP!**

SENDER
ADDRESS
abc.def@ghi.xy
matches pattern
?

./control/badmailfrom

no

yes → **STOP!**

SENDER
ADDRESS
[abc.def]@ghi.xy
in my list
?

./control/badmailpatterns

no

yes → **STOP!**

RECEIPIENT
ADDRESS
[no.one]@fake.com
in my list
?

./control/badrcptto

no →

RECEIPIENT
ADDRESS
no.one@fake.com
matches pattern
?

yes → **STOP!**

./control/badrcptpatterns

no

qmail-queue